

Google EDLA CERTIFIED



KAPMAX PREMIUM PRO 14 EDLA INTERACTIVE DIGITAL BOARDS



**ANDROID 14 UPGRADABLE
TO ANDROID 16**



CAMERA MODULE



**8 ARRAY
MICROPHONE**



AI SOFTWARE



**OCTACORE
PROCESSOR**



NFC



**K12 EDUCATIONAL
CONTENT**



**3D IMAGES &
SIMULATIONS**



**EXPANDABLE
UPTO 1 TB**



SPECIFICATIONS

PANEL	SIZE	RESPOND TIME	VISUAL RATIO	PANEL TYPE	DISPLAY COLOURS
	75"	<2.0ms	16:09	LCD/LED	1.07G(8 BITS+ FRC)
	FREQUENCY	MAX VISUAL AREA	RESOLUTION	PIXEL PITCH	COLOUR SATURABILITY
	60 Hz	1649.66(H)x927.93(V)mm	3840X2160		70% NTSC
	BRIGHTNESS	LIFE SPAN	CONTRAST RATIO	LIGHT SOURCE	VIEW ANGLE
	400cd/m2(+10%)	>50,000 Hr.	1200:01:00	DLED	LCD/LED

MICROPHONE & NFC	FRONT BUILDS IN	-	NFC
	8 ARRAY MICROPHONE AND 06mtr PICKUP DISTANCE	-	SCREEN SHARING AND DATA TRANSFER

AUDIO/VIDEO PARAMETERS	SPEAKERS	SOUND TRACK	POWER	SUBWOOFER
		2.1 CHANNEL	15 X 2 WATT	20 WATT

TOUCH PARAMETERS	TOUCH SPECIFICATIONS	SUPPORT SYSTEM		OUTPUT CO-ORDINATES	
	NON-CONTACT INFRARED SENSING TECHNOLOGY	WINDOWS 10/WINDOWS 8/WINDOWS 11 /ANDROID/LINUX/MAC OS X/CHROME		32767(W) X 32767(D)	
	TOUCH POINTS	Min. IDENTIFIER	WRITING DISPLAY		WRITING HEIGHT
	64	2mm	SINGLE STYLUS PEN 2 COLOR		MAX 400W
	RESPOND TIME	TOUCH DEPTH	INPUT MODE		
	<20ms	±1mm(OVER 90% AREA)	OPAQUE OBJECT(FINGURE,PEN etc)		

SYSTEM	VERSION	CPU	CPU Mali-G52MP8	RAM	ROM
	ANDROID 14.0	A73*4+A53*4	(8EE)	8GB	128GB

WIRELESS	BLUETOOTH	VERSION	WORKING FREQUENCY	WORKING DISTANCE	REMARK VIA
		5	2.4/5Ghz	10 mtr	
	WIFI	VERSION	WORKING FREQUENCY	WORKING DISTANCE	REMARK VIA
		6	2.4/5Ghz	10 mtr	

REAR I/O INTERFACE	MIC IN	USB2.0	USB 3.0	HDMI IN	USB TOUCH OUT
	1	1	1	2	1
	HDMI OUT	OPTICAL OUT	LAN RJ 45 IN	LINE OUT	RS232
	1	1	1	1	1
	TF CARD				
	1				

FRONT INTERFACE	USB 3.0	TOUCH USB	HDMI IN	TYPE-C
	2	1	1	1

POWER	VOLTAGE	MAX. POWER CONSUMPTION	STAND BY POWER CONSUMPTION
	100-240 AC 50/60Hz 4A	280W	≤0.5W

STRUCTURE	BARE DIMENSION	PACKING DIMENSION	MACHINE+WALL MOUNT THICKNESS	VESA HOLE SITE
	1707 X 91.8 X 1022.7 mm	1873 X 270 X 1197mm	118mm (WIB9060G)	800 X 400 mm
	NET WEIGHT	GROSS WEIGHT	WALL MOUNTING SCREW SPECIFICATION	
	61.8KG	81.3KG	M8 X 25mm	

ENVIRONMENT	WORKING TEMPERATURE	WORKING HUMIDITY	STORAGE TEMPERATURE	STORAGE HUMIDITY	WORKING ELEVATION
	0°C-40°C	10%-90%RH	-20°C-60°C	10%-90%RH	<5000m

Learn More: www.kapmax.com

Contact Us: sales@kapmax.com

Follow Us: www.youtube.com/@KapmaxTechnologies

<https://www.facebook.com/Kapmaxtech/>

<https://www.linkedin.com/company/kapmax/>

<https://www.instagram.com/kapmaxtech/?hl=en>